



GSV1015

HDMI1.4 HDCP1.4 Receiver with TTL/LVDS
Output and Audio Extraction

September, 2019

PRODUCT SPECIFICATION

深圳市昂纬科技有限公司
17688724040
www.onwaytech.com
vera.huang@onwaytech.com

1 General Information

1.1 General Information

The GSV1015 is a HDMI1.4 compatible RX receiver with LVDS/TTL data bus, and supports HDCP 1.4. For audio extraction, GSV1015 can support up to 8-channel I2S/2-channel S/PDIF/TDM.

The HDMI input maximum processing pixel clock frequency is 300MHz which means the video resolution can support up to 4kx2k@30Hz 4:4:4 8-bit. The maximum processing audio sample frequency is 8-channel 192K Hz for non-compression timing.




Figure 1 top diagram

Internal video processing supports CSC/ Dither/ 420<->444 conversion/ Downscaler/ Deinterlacer/ LVDS and TTL Pin Mapping. Figure 2 is its diagram.




Figure 2 video datapath diagram

Audio TTL output pins support audio format listed in Table 1.

Table 1. Supported Audio Format

Packet ID	Packet Type	Sample Frequency or Frame Rate		
		32.0, 44.1, 48.0, 88.2, 96.0, 176.4, and 192.0 kHz	256.0, 352.8, 384.0, 512.0, 705.6, 768.0 kHz	64.0 and 128.0 kHz
0x02	Audio Sample (L-PCM and IEC 61937 compressed formats)	Y	N	Y
0x07	One Bit Audio Sample Packet	Y	N	N
0x08	DST Audio Packet	Y	N	N
0x09	High Bitrate Audio Stream Packet (IEC 61937)	N	Y	N

An internal Clock Generator can be used to generate 4 independent output clocks, which will greatly remove complexity of using dedicated clock device.

1.2 Features

1.2.1 HDMI RX receiver

- Compliant with HDMI1.4b
- Compliant with HDCP1.4
- Data rate up to 9Gbps
- Adaptive receiver equalization
- AC-coupling capable
- UDP bus to support the combination of video/audio/info-frames
- Color Space Converter supports any conversion between different color spaces
- HDR supported (HDR10/HDR12/Dolby Vision/HLG)
- 5V tolerance on DDC/HPD/CEC

1.2.2 Multi-Port LVDS Transmitter

- Bi-directional LVDS, supports video format up to 4K 30 444
- Compatible with series FPGAs, LVDS standard (15 pairs in maximum)
 - ◆ Programmable output swing, slew-rate, common voltage and pre-emphasis
 - ◆ SDR/DDR/xN (N = 1~7) LVDS Clock transmitter with configurable output phase
 - ◆ Data rate up to 1.5Gbps per lane
 - ◆ Differential HS/VS/DE available
 - ◆ Embedded SAV/EAV mode supported
- Compatible with VESA and JEIDA standards
 - ◆ Single/Dual-Port LVDS Transmitter
 - ◆ Programmable output swing, slew-rate, common voltage and pre-emphasis
 - ◆ Data rate up to 1.5Gbps per lane

1.2.3 Compatible TTL Transmitter

- 48bit TTL Video Output
 - ◆ Programmable drive strength, slew-rate, driver disabled state control
 - ◆ SDR/DDR Clock Output with configurable output phase
 - ◆ Data rate up to 300Mbps per lane
 - ◆ HS/VS/DE available
 - ◆ Embedded SAV/EAV mode supported
 - ◆ 1.8/2.5/3.3V VCCO compatible.

1.2.4 Audio Output

- ◆ SPDIF/I2S/HBR/DSD/TDM Audio Extraction

1.3 Chip Application Modes

1.3.1 HDMI 1.4 RX with LVDS/TTL output mirroring input

The LVDS/TTL Output are mirrored from input with no internal processing. Downscaler/444-420 converter can be used to guarantee the HDMI Tx has the best 4K/2K compatibility with fixed HDMI Rx input timing.




Figure 3 HDMI 1.4 RX with LVDS/TTL output mirroring input

1.3.2 HDMI 1.4 RX with LVDS/TTL output using UDP mode

Patented UDP mode is used to combine input video/audio together onto a single universal bus to minimize the pin number.




Figure 4 HDMI 1.4 RX with LVDS/TTL output using UDP mode

1.3.3 HDMI 1.4 RX with LVDS/TTL output in single color space

Internal IPs could be used to do color space conversion to guarantee the LVDS/TTL output is always in the same color space (either RGB/YCbCr 444/YCbCr422/YCbCr420). If needed, this mode can also downscale all the 4K to 2K for LVDS/TTL Output. This application mode is often used in embedded sync transmission.

5 Package Information




Figure 25. Package Dimensions (BGA144)

6 Ordering Guide

Table 36. Ordering Information

Part Number.	Temperature Range	Package Description	Packing Type
GSV1015	−20 °C to +85 °C	BGA144, 0.8 mm ball pitch, 10 mm x 10 mm outline	Tray

深圳市昂纬科技发展有限公司
17688724040
www.onwaytech.com
vera.huang@onwaytech.com